

AMENDMENTSIn the Claims

1. (Currently Amended) A network device comprising:
a duplicate packet map (DPM), wherein
said DPM comprises a previous time interval field and a current time interval
field; and
a DPM bank, wherein
said DPM bank comprises a plurality of DPMs, and said DPM; ~~and~~
~~a plurality of DPMs, wherein~~
said plurality of DPMs ~~comprise~~ comprises said DPM.
2. (Original) The network device of claim 1, wherein said DPM comprises:
a plurality of DPM fields.
3. (Original) The network device of claim 2, wherein
said DPM is configured to receive a packet summary value (PSV).
4. (Original) The network device of claim 3, wherein said DPM is implemented as a
Bloom filter.
5. (Original) The network device of claim 3, wherein
a one of said DPM fields corresponds to said PSV.
6. (Original) The network device of claim 3, wherein
each of said DPM fields corresponds to a bit in said PSV.
7. (Original) The network device of claim 3, wherein
each of said DPM fields is configured to compare a value of a corresponding bit of said
PSV with a value stored in said each of said DPM fields to generate an output,
and

a value of each of said outputs indicates whether said value of said corresponding bit of said PSV matches said value stored in said each of said DPM fields.

8. (Original) The network device of claim 3, wherein each of said DPM fields is configured to be addressed using said PSV, and a value stored in a one of said DPM fields corresponding to a value of said PSV indicates whether said packet is said duplicate packet.

9. (Original) The network device of claim 1, further comprising: a packet summary value (PSV) generator, wherein said duplicate packet map (DPM) is coupled to said PSV generator.

10. (Original) The network device of claim 9, wherein said PSV generator is configured to generate a PSV based on a packet received by said PSV generator, and said DPM is configured to receive said PSV.

11. (Original) The network device of claim 9, wherein said DPM comprises: a plurality of DPM fields.

12. (Original) The network device of claim 11, wherein a one of said DPM fields corresponds to said PSV.

13. (Original) The network device of claim 11, wherein each of said DPM fields corresponds to a bit in said PSV.

14. (Original) The network device of claim 12, wherein said DPM is implemented as a Bloom filter.

15. (Cancelled)

16. (Cancelled)

17. (Previously Presented) The network device of claim 1, wherein each of said DPMs is implemented as a Bloom filter.
18. (Previously Presented) The network device of claim 1, wherein a first one of said DPMs is designated as a current DPM, and a second one of said DPMs is designated as a previous DPM.
19. (Previously Presented) The network device of claim 1, wherein said DPM bank further comprises:
- a DPM addressing unit coupled to said DPMs;
 - a selection unit coupled to said DPMs; and
 - a DPM control unit, coupled to control said DPM addressing unit, said DPMs and said selection unit.
20. (Original) The network device of claim 19, wherein said DPM control unit is configured to select a first one of said DPMs as a current DPM and a second one of said DPMs as a previous DPM.
21. (Original) The network device of claim 20, wherein said DPM control unit is configured to cause said DPM addressing unit to provide said PSV to said current DPM and said previous DPM; and said DPM control unit is configured to cause said selection unit to select said current DPM and said previous DPM.
22. (Original) The network device of claim 20, wherein said DPM control unit is configured to select said previous DPM as an inactive DPM and to clear said inactive DPM.
23. (Previously Presented) The network device of claim 1, further comprising: a packet summary value (PSV) generator, wherein said duplicate packet map (DPM) is coupled to said PSV generator.

24. (Original) The network device of claim 23, wherein said DPM bank further comprises:
a DPM addressing unit coupled between said PSV generator and said DPMs; and
a selection unit coupled to said DPMs.
25. (Original) The network device of claim 24, wherein said DPM bank further comprises:
a DPM control unit, coupled to control said DPM addressing unit, said DPMs and said selection unit.
26. (Original) The network device of claim 25, wherein
said selection unit is configured to generate a hit signal, and
said hit signal indicates that bit values of said PSV match bit values stored in
corresponding locations in a one of said DPMs.
27. (Original) The network device of claim 9, wherein
said PSV generator is configured to generate a PSV based on a packet received by said
PSV generator, and
said DPM is configured to receive said PSV.
28. (Original) The network device of claim 27, wherein
said DPM is further configured to indicate that said PSV matches a PSV stored in said
DPM.
29. (Original) The network device of claim 28, wherein said PSV generator is
configured to generate said PSV using a cyclic redundancy check computation.
30. (Original) The network device of claim 9, further comprising:
a packet processing unit, said packet processing unit comprising said PSV generator.
31. (Original) The network device of claim 30, further comprising:
a DPM bank, wherein
said DPM bank comprises said DPM,

said DPM bank is configured to generate a hit signal, and
 said DPM bank is coupled to receive said PSV from said PSV generator and to
 provide said hit signal to said packet processing unit.

32. (Original) The network device of claim 31, wherein
 said hit signal indicates that a value of said PSV matches a value stored in a one of said
 DPMs.
33. (Original) The network device of claim 31, wherein
 said hit signal indicates that bit values of said PSV match bit values stored in
 corresponding locations in a one of said DPMs.
34. (Original) The network device of claim 31, wherein
 said packet processing unit is configured to process said packet using said hit signal.
35. (Original) The network device of claim 31, wherein
 said processing includes causing said packet processing unit to drop said packet based on
 said hit signal.
36. (Currently Amended) A method comprising:
~~determining if a packet is a duplicate packet, wherein the determining comprises~~
 determining if a field of a duplicate packet map (DPM) indicates ~~said a~~ packet is
 a duplicate packet, wherein said DPM is one of a plurality of DPMs
included in a DPM bank and said determining uses determination is
~~made using a DPM, a DPM bank, a plurality of and~~ a packet summary
 value (PSV) corresponding to said packet, and
 said DPM comprises a previous time interval field and a current time
 interval field.
37. (Original) The method of claim 36, further comprising:
 indicating said packet is said duplicate packet, if said determination determines said
 packet is said duplicate packet.

38. (Original) The method of claim 37, further comprising:
dropping said packet, if said packet is said duplicate packet.
39. (Previously Presented) The method of claim 37, wherein said determining comprises:
comparing said PSV to said DPM.
40. (Original) The method of claim 39, wherein
said determination is made by comparing a bit of said PSV with a bit stored in said field
of said DPM, and
said indicating is performed if said bit of said PSV matches said bit stored in said field of
said DPM.
41. (Original) The method of claim 40, further comprising:
setting said bit stored in said field of said DPM to a value of said bit of said PSV.
42. (Original) The method of claim 37, wherein said determining comprises:
selecting said field of said DPM based on said PSV.
43. (Original) The method of claim 42, wherein
said determination is made by selecting said field of said DPM based on a value of said
PSV, and
said indicating is performed if a value stored in said field of said DPM indicates that said
packet is said duplicate packet.
44. (Original) The method of claim 43, further comprising:
setting said value stored in said field of said DPM, if said packet is not said duplicate
packet.
45. (Original) The method of claim 44, further comprising:
generating said PSV by generating a cyclic redundancy check value based on information
in said packet.

46. (Cancelled)

47. (Currently Amended) The method of claim [[46]] 37, further comprising:
selecting a first DPM of said plurality of DPMs as a previous DPM; and
selecting a second DPM of said plurality of DPMs as a current DPM.

48. (Original) The method of claim 47, further comprising:
determining if a field of said previous DPM indicates said packet is said duplicate packet,
using said PSV; and
determining if a field of said current DPM indicates said packet is said duplicate packet,
using said PSV.

49. (Original) The method of claim 48, further comprising:
indicating said packet is not said duplicate packet, if said field of said previous DPM
indicates said packet is not said duplicate packet and said field of said current
DPM indicates said packet is not said duplicate packet, and
indicating said packet is said duplicate packet, otherwise.

50. (Original) The method of claim 47, further comprising:
selecting said previous DPM as an inactive DPM;
selecting said current DPM as said previous DPM; and
selecting another DPM of said DPMs as said current DPM.

51. (Original) The method of claim 50, further comprising:
clearing said inactive DPM prior to said inactive DPM being selected as said current
DPM.

52. (Original) The method of claim 50, wherein
said selecting said previous DPM as said inactive DPM, said selecting said current DPM
as said previous DPM, and said selecting said another DPM of said DPMs as said
current DPM are performed periodically.

53. (Original) The method of claim 52, wherein
a period of said performing periodically is such that said period is greater than an
expected differential between duplicate packet arrivals and said period is less than
a time between packet retransmissions.
54. (Original) The method of claim 52, wherein
a period of said performing periodically is configured to allow said inactive DPM to be
cleared prior to said inactive DPM being selected as said current DPM.
55. (Currently Amended) A network device comprising:
a processor;
computer readable medium coupled to said processor; and
computer code, encoded in said computer readable medium, ~~for determining if a packet~~
~~is a duplicate packet and~~ configured to cause said processor to:
determine if a field of a duplicate packet map (DPM) indicates said packet is a
duplicate packet, wherein said DPM is one of a plurality of DPMs
included in a DPM bank and
said computer code configured to cause said processor to determine uses a
~~DPM, a DPM bank, a plurality of DPMs, and~~ a packet summary
value (PSV) corresponding to said packet, and
said DPM includes a previous time interval field and a current time
interval field.
56. (Original) The network device of claim 55, wherein said computer code is further
configured to cause said processor to:
indicate said packet is said duplicate packet, if said computer code configured to cause
said processor to determine determines said packet is said duplicate packet.
57. (Original) The network device of claim 56, wherein said computer code is further
configured to cause said processor to:
compare said PSV to said DPM.

58. (Original) The network device of claim 56, wherein said computer code is further configured to cause said processor to:

select said field of said DPM based on said PSV.

59. (Original) The network device of claim 58, wherein said computer code is further configured to cause said processor to:

generate said PSV by virtue of being configured to generate a cyclic redundancy check value based on information in said packet.

60. (Cancelled)

61. (Currently Amended) The network device of claim [[60] 55, wherein said computer code is further configured to cause said processor to:

select a first DPM of said DPMs as a previous DPM; and

select a second DPM of said DPMs as a current DPM.

62. (Original) The network device of claim 61, wherein said computer code is further configured to cause said processor to:

determine if a field of said previous DPM indicates said packet is said duplicate packet, using said PSV; and

determine if a field of said current DPM indicates said packet is said duplicate packet, using said PSV.

63. (Original) The network device of claim 62, wherein said computer code is further configured to cause said processor to:

indicate said packet is not said duplicate packet, if said field of said previous DPM indicates said packet is not said duplicate packet and said field of said current DPM indicates said packet is not said duplicate packet, and
indicate said packet is said duplicate packet, otherwise.

64. (Original) The network device of claim 61, wherein said computer code is further configured to cause said processor to:

select said previous DPM as an inactive DPM;

select said current DPM as said previous DPM; and
 select another DPM of said DPMs as said current DPM.

65. (Original) The network device of claim 64, wherein
 said computer code further configured to cause said processor to select said previous
 DPM as said inactive DPM, said computer code further configured to cause said
 processor to select said current DPM as said previous DPM, and said computer
 code further configured to cause said processor to select said another DPM of said
 DPMs as said current DPM are further configured to be performed periodically.

66. (Original) The network device of claim 65, wherein
 a period of said performing periodically is such that said period is greater than an
 expected differential between duplicate packet arrivals and said period is less than
 a time between packet retransmissions.

67. (Original) The network device of claim 65, wherein
 a period of said performing periodically is configured to allow said inactive DPM to be
 cleared prior to said inactive DPM being selected as said current DPM.

68. (Currently Amended) A computer program product ~~for determining if a
 packet is a duplicate packet,~~ comprising:
 a first set of instructions, executable on a computer system, configured to determine if a
 field of a duplicate packet map (DPM) indicates a packet is said duplicate packet,
 wherein said DPM is one of a plurality of DPMs included in a DPM bank and
 said first set of instructions makes said determination using ~~a DPM, a DPM~~
~~bank, a plurality of DPMs, and~~ a packet summary value (PSV)
 corresponding to said packet, and
 said DPM comprises a previous time interval field and a current time interval
 field; and
 computer readable storage media, wherein said computer program product is encoded in
 said computer readable storage media.

69. (Original) The computer program product of claim 68, further comprising:
a second set of instructions, executable on said computer system, configured to indicate
said packet is said duplicate packet, if said computer code configured to cause
said processor to determine determines said packet is said duplicate packet.
70. (Original) The computer program product of claim 69, further comprising:
a third set of instructions, executable on said computer system, configured to compare
said PSV to said DPM.
71. (Original) The computer program product of claim 69, further comprising:
a third set of instructions, executable on said computer system, configured to select said
field of said DPM based on said PSV.
72. (Original) The computer program product of claim 71, further comprising:
a fourth set of instructions, executable on said computer system, configured to generate
said PSV by virtue of being configured to generate a cyclic redundancy check
value based on information in said packet.
73. (Cancelled)
74. (Currently Amended) The computer program product of claim ~~[[73]]~~ 68, further
comprising:
a second set of instructions, executable on said computer system, configured to select a
first DPM of said DPMs as a previous DPM; and
a third set of instructions, executable on said computer system, configured to select a
second DPM of said DPMs as a current DPM.
75. (Original) The computer program product of claim 74, further comprising:
a fourth set of instructions, executable on said computer system, configured to determine
if a field of said previous DPM indicates said packet is said duplicate packet,
using said PSV; and

a fifth set of instructions, executable on said computer system, configured to determine if a field of said current DPM indicates said packet is said duplicate packet, using said PSV.

76. (Original) The computer program product of claim 75, further comprising:

a sixth set of instructions, executable on said computer system, configured to indicate said packet is not said duplicate packet, if said field of said previous DPM indicates said packet is not said duplicate packet and said field of said current DPM indicates said packet is not said duplicate packet, and

a seventh set of instructions, executable on said computer system, configured to indicate said packet is said duplicate packet, otherwise.

77. (Original) The computer program product of claim 74, further comprising:

a fourth set of instructions, executable on said computer system, configured to select said previous DPM as an inactive DPM;

a fifth set of instructions, executable on said computer system, configured to select said current DPM as said previous DPM; and

a sixth set of instructions, executable on said computer system, configured to select another DPM of said DPMs as said current DPM.

78. (Original) The computer program product of claim 77, wherein

said fourth, said fifth, and said sixth set of instructions are performed periodically.

79. (Previously Presented) The computer program product of claim 78, wherein

a period of said performing periodically is such that said period is greater than an expected differential between duplicate packet arrivals and said period is less than a time between packet retransmissions.

80. (Previously Presented) The computer program product of claim 78, wherein

a period of said performing periodically is configured to allow said inactive DPM to be cleared prior to said inactive DPM being selected as said current DPM.

81. **(Currently Amended)** An apparatus comprising:

means for determining if a field of a duplicate packet map (DPM) indicates a packet is a duplicate packet, wherein said DPM is one of a plurality of DPMs included in a DPM bank and

said means for determining uses ~~a DPM, a DPM bank, a plurality of DPMs,~~
~~and~~ a packet summary value (PSV) corresponding to said packet, and
 said DPM comprises a previous time interval field and a current time interval field;

means for indicating said packet is said duplicate packet, said means for indicating configured to indicate said packet is said duplicate packet if said means for determining determines said packet is said duplicate packet; and
 means for selecting said field of said DPM based on said PSV.

82. **(Cancelled)**

83. **(Previously Presented)** The apparatus of claim 81, wherein said determining comprises:

means for comparing said PSV to said DPM.

84. **(Cancelled)**

85. **(Previously Presented)** The apparatus of claim 81, further comprising:

means for generating said PSV comprising a means for generating a cyclic redundancy check value based on information in said packet.

86. **(Cancelled)**

87. **(Currently Amended)** The apparatus of claim ~~[[86]]~~ 81, further comprising:

means for selecting a first DPM of said DPMs as a previous DPM; and
 means for selecting a second DPM of said DPMs as a current DPM.

88. (Original) The apparatus of claim 87, further comprising:
means for determining if a field of said previous DPM indicates said packet is said duplicate packet, using said PSV; and
means for determining if a field of said current DPM indicates said packet is said duplicate packet, using said PSV.
89. (Original) The apparatus of claim 88, further comprising:
means for indicating said packet is not said duplicate packet, if said field of said previous DPM indicates said packet is not said duplicate packet and said field of said current DPM indicates said packet is not said duplicate packet, and
means for indicating said packet is said duplicate packet, otherwise.
90. (Original) The apparatus of claim 87, further comprising:
means for selecting said previous DPM as an inactive DPM;
means for selecting said current DPM as said previous DPM; and
means for selecting another DPM of said DPMs as said current DPM.
91. (Original) The apparatus of claim 90, further comprising:
means for clearing said inactive DPM prior to said inactive DPM being selected as said current DPM.
92. (Original) The apparatus of claim 90, wherein
said means for selecting said previous DPM as said inactive DPM, said means for selecting said current DPM as said previous DPM, and said means for selecting said another DPM of said DPMs as said current DPM perform their respective selections periodically.